

Solid lighting, saving energy



PILA wall-mounted

PILA batten

PILA waterproof

PILA floodlight

PILA

An established brand

Pila is the answer to the needs of those customers who are looking for affordable and yet reliable LED products. Our LED lamps and luminaires are an excellent replacement for their conventional equivalents.

Benefits:

- Affordable/economical products
- Efficient
- Product portfolio dedicated to basic applications
- Guaranteed luminous flux and durability
- Simple conversion from conventional luminaires to LED
- Simple and quick assembly

The factory in Pila started production of traditional bulbs in 1958. Due to the transformation of technology into LED, the first LED Pila LED bulbs appeared on the market in 2014 and LED tubes in 2017.

In some European markets, Pila is a brand with high reputation and awareness among consumers (34% source: HeartBeat) and it's highly recognized in the professional market among installers.

Therefore, in 2018, we decided to expand the offer with a full category of economical professional installation fittings.

PILA wall-mounted



Specifications

**PILA WL007C LED14S/740
PSU OVL WH**



Product description

PILA WL007C LED14S/740
PSU OVL WH

Light output (lm)

1400

Power (W)

15

CCT (K)

4000

Mains voltage

220-240V / 50-60Hz

Lifetime

35,000 hrs

CRI

70

Connection

Screw terminal

IP rating

IP65 / IP54 (MDU version)

Power factor

> 0.9

Safety class

Class II

Housing material

Polycarbonate

Color

White

EOC

8710163335100

12NC

911401735142

Specifications

**PILA WL007C LED13S/740
PSU RND MDU WH**



PILA WL007C LED13S/740
PSU RND MDU WH

1300

15

4000

220-240V / 50-60Hz

35,000 hrs

70

Screw terminal

IP65 / IP54 (MDU version)

> 0.9

Class II

Polycarbonate

White

8710163335117

911401735132

Benefits wall mount oval

- ▶ Wall and ceiling mounted
- ▶ Energy efficient

Benefits wall mount round

- ▶ Wall and ceiling mounted
- ▶ Energy efficient
- ▶ Movement detection unit



PILA batten

Specifications

PILA BN007C LED32S/840
PSU L1200



Product description	PILA BN007C LED32S/840 PSU L1200
Light output (lm)	3200
Power (W)	32
CCT (K)	4000
Mains voltage	220-240V / 50-60Hz
Lifetime	35,000 hrs
CRI	80
Connection	Fly wire 0.15m
IP rating	IP20
Power factor	> 0.9
Safety class	Class I
Housing material	Glass/Aluminium
Color	White
EOC	8710163335087
12NC	911401735152


- ### Benefits
- ▶ Wide application range
 - ▶ Energy efficient



PILA waterproof

Specifications

PILA WT007C LED34S/840
PSU L1200



Specifications

PILA WT007C LED54S/840
PSU L1500



Product description	PILA WT007C LED34S/840 PSU L1200	PILA WT007C LED54S/840 PSU L1500
Light output (lm)	3400	5400
Power (W)	34	54
CCT (K)	4000	4000
Mains voltage	220-240V / 50-60Hz	220-240V / 50-60Hz
Lifetime	35,000 hrs	35,000 hrs
CRI	80	80
Connection	Wire	Wire
IP rating	IP65 / IK06	IP54 / IK06
Power factor	> 0.9	> 0.9
Safety class	Class II	Class II
Housing material	Polycarbonate	Polycarbonate
Color	Grey	Grey
EOC	8710163335148	8710163335155
12NC	911401735772	911401735782

Benefits

- Robust
- For all industrial applications



PILA floodlights

Specifications

PILA BVP007
10W 4000k



Specifications

PILA BVP007
20W 4000k



Specifications

PILA BVP007
50W 4000k



Product description	PILA BVP007 10W 4000k	PILA BVP007 20W 4000k	PILA BVP007 50W 4000k
Light output (lm)	850	1700	4250
Power (W)	10	20	50
CCT (K)	4000	4000	4000
Mains voltage	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz
Lifetime	35,000 hrs	35,000 hrs	35,000 hrs
CRI	70	70	70
Connection	Flying wire	Flying wire	Flying wire
IP rating	IP65 / IK06	IP65 / IK06	IP65 / IK06
Power factor	> 0.9	> 0.9	> 0.9
Safety class	Class I	Class I	Class I
Housing material	Glass/Aluminium	Glass/Aluminium	Glass/Aluminium
Color	Black	Black	Black
EOC	8710163329871	8710163329888	8710163329895
12NC	911401732202	911401732212	911401732222

Benefits

- ▶ Energy saving
- ▶ Robust luminaire
- ▶ Reliable quality

Specifications

PILA BVP007
10W 3000k

Specifications

PILA BVP007
20W 3000k

Specifications

PILA BVP007
50W 3000k

Product description	PILA BVP007 10W 3000k	PILA BVP007 20W 3000k	PILA BVP007 50W 3000k
Light output (lm)	800	1600	4000
Power (W)	10	20	50
CCT (K)	3000	3000	3000
Mains voltage	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz
Lifetime	35,000 hrs	35,000 hrs	35,000 hrs
CRI	70	70	70
Connection	Flying wire	Flying wire	Flying wire
IP rating	IP65 / IK06	IP65 / IK06	IP65 / IK06
Power factor	> 0.9	> 0.9	> 0.9
Safety class	Class I	Class I	Class I
Housing material	Glass/Aluminium	Glass/Aluminium	Glass/Aluminium
Color	Black	Black	Black
EOC	8710163329901	8710163329918	8710163329925
12NC	911401732232	911401732242	911401732252

Benefits

- ▶ Energy saving
- ▶ Robust luminaire
- ▶ Reliable quality

Specifications

PILA BVP007 20W
4000k MDU

Specifications

PILA BVP007 50W
4000k MDU

Product description	PILA BVP007 20W 4000k MDU	PILA BVP007 50W 4000k MDU
Light output (lm)	1700	4250
Power (W)	20	50
CCT (K)	4000	4000
Mains voltage	220-240V / 50-60Hz	220-240V / 50-60Hz
Lifetime	35,000 hrs	35,000 hrs
CRI	70	70
Connection	Flying wire	Flying wire
IP rating	IP65 / IK06	IP65 / IK06
Power factor	> 0.9	> 0.9
Safety class	Class I	Class I
Housing material	Glass/Aluminium	Glass/Aluminium
Color	Black	Black
EOC	871016332994999	871016332995699
12NC	911401732272	911401732282

Benefits

- ▶ Energy saving
- ▶ Robust luminaire
- ▶ Reliable quality





PILA
I.B.R.S. / C.C.R.I. Nummer 10461
5600 VB Eindhoven
The Netherlands

www.pila-led.com

©2019 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.